



Project goal

In the Pilot-SBG project, a possible process chain has been set up as a pilot-scale biorefinery to produce methane as a fuel from biogenic residues. Biogenic residues and waste materials are first converted into biogas, which essentially consists of methane (CH₄) and carbon dioxide (CO₂). Catalyst-damaging components such as hydrogen sulphide (H₂S) are then separated and the CO₂ is catalytically hydrogenated by adding hydrogen (H₂) without prior separation. This refines the biogas into biomethane and achieves a significantly higher biomethane yield and CO₂ reduction compared to conventional methods.

Reactor design

- Reactor type: Fixed bed
- Volume: 570 ml
- Temperature: up to 500 °C
- Pressure: up to 20 bar(g)
- Electrical heating and air cooling in three segments




Fig. 2: Schematic structure of the methanation reactor



Scan the QR code and find our focus booklet 'Methanation' with more information on the topic and a direct comparison of biological and catalytic methanation.



www.dbfz.de/en/pilot-sbg



This publication was carried out on behalf of the Federal Ministry for Digital and Transport under file number 3552.1. The sole responsibility for the content lies with the author.




Fig. 1: Methanation module in the pilot plant with two adsorber vessels and a methanation reactor



Start-up process

Operating parameters: Catalyst: Ru on Al₂O₃

- Biogas volume flow = 50 L/h
- Reactor pressure = 18 bar(g)
- Reactor target temperature = 320 °C
- H₂/CO₂ ratio = 4

Measurement of the product gas composition using an on-line micro gas chromatograph.

Temperatures in the reactor




Fig. 4: Course of the reactor temperatures in the start-up process of the catalytic methanation of biogas

Biogas composition




Fig. 3: Biogas composition in the storage tank at the start of the experiment

Product gas composition




Fig. 5: Course of the product gas composition in the start-up process of the catalytic methanation of biogas

Outlook

As part of a statistical test programme, the optimum operating conditions are determined for two selected catalysts as a function of temperature, room speed and H₂/CO₂ ratio. Whether the catalysts are

also economically viable is analysed on the basis of an economic and ecological assessment, taking into account the H₂S tolerance of the catalysts.




Fig. 5: Design of experiment for the catalyst evaluation