

Operation of a pilot scale biorefinery

for renewable methane and value adding by-products

Philipp Knötig, Philipp Wilker, Bomin Yuan, Theresa Menzel, Marcel Pohl, Christian Klüpfel - Pilot-SBG, Deutsches Biomasseforschungszentrum gemeinnützige GmbH

EUBCE 2025, 3BO.9, 10.06.2025 Valencia

On behalf of:



Federal Ministry
of Transport

Catalytic Methanation

Substrate preparation

Gas storage

HTP (pre-)treatment of substrates and digestates


Digestate processing and recovery of valuable by-products

**Anaerobic fermentation
(continuous stirring tank and plug flow reactor)**

Pilot plant and process scope

Commercial scale concepts

Raw materials (straw/manure 50/50)
51,520 t/a
Hydrogen
1,840 t/a



Biogas
16,000 t/a
Fertilizer
98,240 t/a (s/l)
**

Methane
8,800 t/a



More research on upscaling, economics, educt potentials etc.



input
Raw materials
7-8 t/a
Hydrogen
0.18-0.26 t/a
(2000-2900 m³/a)


Pilot plant

output
Biogas
≈ 1 t/a
(≈ 770 m³/a)
Methane
0.59-0.67 t/a
(819-930 m³/a)
Fertilizer
5-7 t/a (s/l)
Hydrochar
≈ 2 t/a
*

Est. potential¹

450 PJ/a straw & cattle manure	36%
75 PJ/a green and bio waste	Total diesel consumption in Germany

m³ - standard cubic metre; * Rough approximation from the mass balance. Biogas, fertiliser and hydrochar amount and composition depend on the raw material origin and quality; **for the first commercial size plant concept results from lab scale preliminary tests were used since the pilot plant was still in commissioning.



Input materials





Anaerobic fermentation | Line 2



Anaerobic fermentation | Line 1



Operation of a pilot scale biorefinery


Anaerobic digestion

Comparison of two reactor lines

Inputs:
Wheat straw
Cow manure


Biomass

Dry matter fed:
PFR: 15 %_{FM}
CSTR: 8 %_{FM}





Operation of the anaerobic digestion

PFR





CSTR




Operation of a pilot scale biorefinery

Anaerobic digestion



Operation of a pilot scale biorefinery

Digital twin (AD)



- Kinetic process simulation of pilot plant in SuperPro Designer
 - Biogas kinetics adapted from ADM1-R4¹ & validated
 - overall deviation $\leq 1 \%$
- Base for Scale Up, concept evaluation & comparison for different process operations


Equivalent conditions	
Manure: Straw	3:1 [FM]
Total solids	8 %
C/N	20



Operation of a pilot scale biorefinery

Catalytic methanation



Layout & design




Operation of a pilot scale biorefinery

Catalytic methanation

Start-up process






$Ru2/Al_2O_3$, $T = 320 \text{ } ^\circ C$, $p = 18 \text{ bar(g)}$, $H_2:CO_2 = 4$, $\dot{V}_{\text{biogas}} = 60 \text{ L/h}$, $GHSV = 449 \text{ h}^{-1}$



Operation of a pilot scale biorefinery

Catalytic methanation

Previous parameters



Ru2/Al₂O₃, T = 320 °C, p = 18 bar(g), H₂:CO₂ = 4, $\dot{V}_{\text{biogas}} = 60 \text{ L/h}$, GHSV = 449 h⁻¹


*Energy efficiency determined from calorific value of product and educt




Operation of a pilot scale biorefinery

Digestate treatment

Results from commissioning phase:



Quantitative evaluation of its effect on methane production



- The experiment data were statistically evaluated
- Digestate recirculation increased methane production by $8.24 \pm 0.35\%$ compared to the reference reactors
- It significantly reduced the demand for fresh water and urea
- Decrease of possible waste streams and thus energy intensive cleaning tech.




Hydrothermal (pre-)treatment


Hydrothermal pre-treatment and carbonization, commissioning

Input




Biomass



Digestate



Conversion



Output

to digester



Hydrochar

Status

- We can show an automated 24/7 production of advanced biofuels in an integrated pilot plant

Outlook

- Operation and research campaigns until 12/2026
 - E.g. update of evaluations on commercial size biorefinery
 - Open data

New projects: e.g. FlexBiorefinery (FlexBioref)

- Demand based supply of energy or chemicals (Methanol/Methane) through autonomous decision making
- Looking for partners



Visit us at our stand 07.
or find me on the EUBCE app

Technical overview

Research & demonstration platform

Innovation | Research | Development

Methanation

Digestate treatment

Anaerobic fermentation

Hydrothermal processes

Substrate preparation and storage

The booklet features a cover image of a complex industrial facility with various pipes, tanks, and machinery. The title 'RESEARCH & DEMONSTRATION PLATFORM' is prominently displayed, along with the words 'Innovation / Research / Development'. The back cover contains a section titled 'Technical data' with tables for Nominal volume (500L), Working temperature (Up to 240 °C), Working pressure (Up to 40 bars), and Heating (Electric). A QR code is located at the bottom right of the booklet cover.

Download:

A large QR code is provided for easy access to the booklet's digital version.

Technical details, processes and application



Visit us at our stand 07.
or find me on the EUBCE app

Interested?
Contact me!

Philip Knötig

Department Biorefinery

Scientific and Technical Coordinator of the pilot plant Pilot-SBG

Deutsches Biomasseforschungszentrum gGmbH

Torgauer Straße 116

D-04347

Leipzig

Philipp.Knoetig@dbfz.de

+49 (0)341 2434-448

www.dbfz.de/pilot-sbg

